

**15A NCAC 13A .0107 STANDARDS APPLICABLE TO GENERATORS OF HAZARDOUS WASTE - PART 262**

- (a) 40 CFR 262.1 through 262.18 (Subpart A), "General" are incorporated by reference including subsequent amendments and editions. In addition, a small quantity generator shall maintain aisle space of at least two feet in a central accumulation area to allow the unobstructed movement of personnel, fire prevention equipment, spill control equipment, and decontamination equipment.
- (b) 40 CFR 262.20 through 262.27 (Subpart B), "Manifest Requirements Applicable to Small and Large Quantity Generators" are incorporated by reference including subsequent amendments and editions.
- (c) 40 CFR 262.30 through 262.35 (Subpart C), "Pre-Transport Requirements Applicable to Small and Large Quantity Generators" are incorporated by reference including subsequent amendments and editions.
- (d) 40 CFR 262.40 through 262.44 (Subpart D), "Recordkeeping and Reporting Applicable to Small and Large Quantity Generators" are incorporated by reference including subsequent amendments and editions. In addition, a generator shall keep records of inspections and results of inspections required by Section 40 CFR 262.16 and 262.17 for three years from the date of the inspection.
- (e) 40 CFR 262.70 (Subpart G), "Farmers" is incorporated by reference including subsequent amendments and editions.
- (f) 40 CFR 262.80 through 262.89 (Subpart H), "Transboundary Movements of Hazardous Waste for Recovery or Disposal" are incorporated by reference including subsequent amendments and editions.
- (g) 40 CFR 262.200 through 262.216 (Subpart K), "Alternative Requirements for Hazardous Waste Determination and Accumulation of Unwanted Material for Laboratories Owned by Eligible Academic Entities" are incorporated by reference including subsequent amendments and editions.
- (h) 40 CFR 262.230 through 262.233 (Subpart L), "Alternative Standards for Episodic Generation" are incorporated by reference including subsequent amendments and editions.
- (i) 40 CFR 262.250 through 262.265 (Subpart M), "Preparedness, Prevention, and Emergency Procedures for Large Quantity Generators" are incorporated by reference with subsequent amendments and editions. In addition, a large quantity generator shall maintain aisle space of at least two feet in a central accumulation area to allow the unobstructed movement of personnel, fire prevention equipment, spill control equipment, and decontamination equipment.
- (j) The Appendix to 40 CFR Part 262 is incorporated by reference including subsequent amendments and editions.

*History Note: Authority G.S. 130A-294(c);  
Eff. November 19, 1980;  
Amended Eff. December 1, 1988; June 1, 1988; August 1, 1987; May 1, 1987;  
Transferred and Recodified from 10 NCAC 10F .0030 Eff. April 4, 1990;  
Amended Eff. August 1, 1990;  
Recodified from 15A NCAC 13A .0008 Eff. August 30, 1990;  
Amended Eff. April 1, 1993; October 1, 1990;  
Recodified from 15A NCAC 13A .0007 Eff. December 20, 1996;  
Amended Eff. July 1, 2016; April 1, 2010; November 1, 2007; January 1, 2007; April 1, 2001;  
August 1, 1998;  
Temporary Amendment Eff. May 30, 2017 (replaced by the rule effective March 1, 2018);  
Readopted Eff. March 1, 2018.*